

HandScan

Read/Write Electronic for RFID Transponders

RF/ID Identification System Components for GEMPLUS Transponders, GemWave 210, 240 and 270, R/O and R/W, Philips I-Code and TI Tag-it

The Read/Write device is mainly used as a hand held reader to identify objects, like cans, beer kegs, and persons or live stock. Or it is used as a fixed device for applications in the factory automation and for access control.



Special Version with trigger switch and build in battery

- Easy to handle, watertight output connector or fixed cable with watertight cable gland
- LED indicator (red/green)
- Works outside, in industrial areas or on vehicles
- watertight, IP67
- Compact design, small size: 40 mm \varnothing x 120 mm + connector or cable gland
- Low power consumption
- integrated antenna
- reading distance up to 50 mm, depends on transponder type

HandScan

Cylindric Read / Write Electronic for GemWave Transponders 40 mm \varnothing x 120 mm, front side antenna	
Type: 2x1E-1581	12 VDC, RS 232, watertight connector
Type: 2x1E-5581	5VDC, RS232, watertight connector
Type: 2x1E-1681	12 VDC, RS 232, cable 1 m
Type: 2x1E-5681	5VDC, RS232, cable 1 m
Type: 2x1E-1980	9 VDC battery, trigger switch, RS 232, watertight connector

- x ... **6** for 125 kHz transponders
- x ... **7** for GemWave from GemPlus
- x ... **8** for I-Code from Philips

Technical data

Interface:	9600 baud, 1 startbit, 8 databits, no parity, 1 stopbit, halfduplex
Technology:	13,56 MHz, R/W time for 2 kBit less than 0,5 sec.
Power supply	12 VDC (9 – 28 VDC) or 5 VDC +/- 5 %, max. 5% ripple
Power consumption	40 mA - 150 mA, depending on antenna design
Operating Temperature	- 20 - + 70 °C
Housing:	Black plastic, round
Aprovals	ETS 300-330 Conformity, meets CE requirements
Protocol's	see separate datasheets